



British Standard:

BS EN 50085-1:2005
BS EN 50085-2-1:2006
VDE Testing and Certification Institute
Test Certificate No. 40040200*

Material Specification:

British Standard: BS EN 10346:2015.

Finish:

Pre Galvanised

Ordering Information:

- Please refer to the following pages or alternatively visit our website below:

<http://www.trenchltd.com>

Product Information: Standard

- All accessories are screwfix
- Combi head screws to suit crosshead or flathead screwdriver
- Connector screws are serrated on the underside of the head to improve earth continuity
- Connector plates are fitted with captive nuts
- Gusseted as standard

Product Information: Tamperproof

- Screws M5x8 T25 Resistorx
- Connector plates are fitted with captive nuts
- Gusseted as standard

Packing Detail:

- 1 x accessory c/w fitted lid
- 4 x connector plates
- All necessary connector screws

Other Options Available:

- Non Gusset
- Powder Coated
- IP4X
- Alternative Width/Height/Material Thickness
- Reducing Bend

* See Technical Data Sheet / Cable Trunking / Pre Galvanised / Lengths / Test Results for Test Data

Cable Trunking / Pre Galvanised / Accessories / 90° Top Cover Bend / Ordering Information / Page 2 of 3

Standard Equal Compartment

Use the codes in the table on page 3 suffixed with **-2EC** for 2 equal compartment or **-3EC** for 3 equal compartment. For example if you require a 2 equal compartment 90° top cover bend to suit trunking 100mm wide x 50mm high the correct code would be **SA4290T-2EC** and for 3 equal compartment the code would be **SA4290T-3EC**.

Standard Unequal Compartment

Use the codes in the table on page 3 suffixed with **-2UEC-xx/xx** for 2 unequal compartment or **-3UEC-xx/xx/xx** for 3 unequal compartment and complete the form using the link below.

90° top cover bends become "handed" in most instances when unequally compartmented so to ensure that we manufacture to your requirements please visit our website & complete the relevant form at the bottom of the page dependant on the number of unequal compartments you require.

<http://www.trenchltd.com/cable-trunking/cable-trunking-accessories/90-degree-top-cover-bend/>

Please note we require a minimum of 25mm width per compartment.

Tamperproof Accessories

Use the ordering information in the table on page 3 alongside the ordering information above and suffix the code with **-SEC**

For example if you require a 2 equal compartment 90° top cover bend to suit 100mm wide x 50mm high tamperproof trunking the correct code would be **SA4290T-2EC-SEC** and for 3 equal compartment the code would be **SA4290T-3EC-SEC**.

Non Gusset Accessories

Use the ordering information in the table on page 3 alongside the ordering information above and suffix the code with **-NG**

For example if you require a 2 equal compartment 90° top cover bend to suit 100mm wide x 50mm high tamperproof trunking the correct code would be **SA4290T-2EC-SEC-NG** and for 3 equal compartment the code would be **SA4290T-3EC-SEC-NG**.

Powder Coated

Please ensure that when requesting a quotation for powder coated products that you have the correct quantities, RAL number and finish (i.e. matt or gloss) in order for us to quote accordingly.

Please note product codes for powder coated items are Non-Standard, however, dimensions & weights on page 3 are still applicable.

IP4X


To achieve IP4X add to each join 1 x Outer U Piece & 1 x Lid Fix Bar - please follow the link below for ordering instructions.

<http://www.trenchltd.com/cable-trunking/ip4x-accessories/>


| Product Code Standard | Dim A (mm) To Suit Width | Dim B (mm) To Suit Height | Dim C (mm) | Dim D (mm) | Single Comp Weight (kg) | Twin Comp Weight (kg) | Three Comp Weight (kg) |
|-----------------------|--------------------------|---------------------------|------------|------------|-------------------------|-----------------------|------------------------|
| SA2290T | 50 | 50 | 109 | N/A | 0.38 | 0.44 | X |
| SA3290T | 75 | 50 | 134 | N/A | 0.49 | 0.57 | 0.64 |
| SA4290T | 100 | 50 | 159 | N/A | 0.62 | 0.71 | 0.80 |
| SA6290T | 150 | 50 | 209 | N/A | 0.94 | 1.05 | 1.15 |
| SA8290T | 200 | 50 | 259 | N/A | 1.66 | 1.79 | 1.92 |
| SA9290T | 225 | 50 | 284 | N/A | 1.94 | 2.08 | 2.22 |
| SA12290T | 300 | 50 | 359 | N/A | 2.91 | 3.09 | 3.26 |
| SA3390T | 75 | 75 | 138 | N/A | 0.59 | 0.70 | 0.81 |
| SA4390T | 100 | 75 | 159 | N/A | 0.73 | 0.85 | 0.98 |
| SA6390T | 150 | 75 | 209 | N/A | 1.06 | 1.22 | 1.37 |
| SA8390T | 200 | 75 | 259 | N/A | 1.82 | 2.01 | 2.19 |
| SA9390T | 225 | 75 | 284 | N/A | 2.12 | 2.31 | 2.51 |
| SA12390T | 300 | 75 | 359 | N/A | 3.12 | 3.36 | 3.61 |
| SA4490T | 100 | 100 | 159 | N/A | 0.86 | 1.02 | 1.18 |
| SA6490T | 150 | 100 | 209 | N/A | 1.21 | 1.41 | 1.61 |
| SA8490T | 200 | 100 | 259 | N/A | 2.01 | 2.25 | 2.49 |
| SA9490T | 225 | 100 | 284 | N/A | 2.32 | 2.57 | 2.83 |
| SA12490T | 300 | 100 | 359 | N/A | 3.36 | 3.68 | 3.99 |
| SA6690T | 150 | 150 | 209 | N/A | 1.46 | 1.75 | 2.04 |
| SA8690T | 200 | 150 | 259 | N/A | 2.35 | 2.70 | 3.05 |
| SA9690T | 225 | 150 | 284 | N/A | 2.67 | 3.05 | 3.43 |
| SA12690T | 300 | 150 | 359 | N/A | 3.79 | 4.25 | 4.71 |
| SA8890T | 200 | 200 | 259 | N/A | 2.73 | 3.19 | 3.65 |
| SA9990T | 225 | 225 | 284 | N/A | 3.26 | 3.82 | 4.37 |
| SA12990T | 300 | 225 | 359 | N/A | 4.47 | 5.16 | 5.84 |
| SA121290T | 300 | 300 | 359 | N/A | 5.26 | 6.16 | 7.06 |

All dimensions are identical for single & compartmented accessories. Approximate weights shown are a nominal value due to material thickness and tolerance and includes body, lid, fixings and separator (s) where applicable. See Page 2 for Equal/Unequal/Tamperproof/IP4X/Non Gusset & Powder Coating Information.

X Denotes not available



Standard



Non Gusset