

## Maxi Trunking Product Data Sheet

Product Range	PVC-U Trunking Systems	<p>Image for reference only</p> 
Description	Feeder and Distribution Trunking System	
Key Features	<p>Square and Rectangular Profiles</p> <p>Tamper Proof Covers</p> <p>Flush Fitting Accessories on larger sizes</p> <p>Fabricated Fittings and Slow Bends</p> <p>Can be sub-divided to carry power and data</p>	
Dimensions	50 x 50mm, 75 x 50mm, 75 x 75mm, 100 x 50mm, 100 x 100mm, 150 x 150mm	
Material(s)	PVCu	
Compliance / Standards(s)	<p>CE &amp; UKCA Marked</p> <p>Low Voltage Directive 2014/35/EU</p> <p>The Electrical Equipment (Safety) Regulations 2016</p> <p>BS 7671:2018</p> <p>BS EN 50085-1:2005+A1:2013</p> <p>BS EN 50085-2-1:2006+A1:2011</p> <p>BS 5733:2010+A1:2014</p> <p>BS EN IEC 60695-2-11:2021</p>	
Packaging	Recyclable	

### Sustainability



We work hard to ensure our products meet the highest standards and are totally committed to the environment and maximising our usage of recycled material within our manufacturing process.

Our white extruded Maxi Trunking PVC-U products are manufactured from a minimum of 80% recycled material and up to 100% recycled content, depending on material availability.

This range is manufactured from PVC-U, a material that is 100% recyclable, is flame retardant and self-extinguishing.