

Suspension hanger



Description

Side suspension support for ceiling installation of Rejiband® mesh tray with threaded rods. It can be used with heights of 35, 60 and 100mm and widths from 100 to 600mm. This product has quick installation and does not require screws for connection to the system. Made from steel, available in various protection systems.

Advantages

It allows its disassembly in a simple way to facilitate the laying of the cables.

Click system allows fast connection of the wire mesh tray without the need of fixings. Greater economy and quick assembly.

Good load capacity. Up to 100 kg per point for the 2-piece / 2- threaded rod set.

CE certified in compliance with the low voltage directive 2014/35 / EU and international product standard IEC 61537

Available in EZ, BC and GC Protection Systems

Savings of 35% in labour and installation time compared to the option with light-duty channel and double rod.

Applications

Suitable for supporting medium loads on ceiling-mounted cable trays with 1 or 2 rods for Rejiband® trays for cable management in electrical and telecommunications installations, industrial installations, infrastructure and civil works and the service sector.

Solutions



Suspension hanger

Main technical characteristics

18	Steel with surface coating	-50 / 150 °C	A1 No combustible	ETIM
----	----------------------------	--------------	-------------------	------

Product data

Ⓢ	Class 61537	Ref	kg/u
PG	Class 3	81000019	0.058
GC	Class 8	81000021	0.060
BK8	Class 8	81000022	0.059

Ⓢ Protection System

- CU - Copper electroplated
- PG - Pregalvanised
- EZ - Electrogalvanised
- BC - Electrogalvanised Bichromate
- BK8 - High Resistance Coating
- GC - Hot Dip Galvanising
- INOX - Stainless Steel
- PT - Polyester Paint
- AL - Aluminum
- LN - Brass or Nickel-plated brass

Ⓜ Insulating materials

- PC+ABS - Halogen Free Polycarbonate + ABS
- PVC - Polyvinyl Chloride
- PP - Halogen Free Polypropylene
- PA6 - Halogen Free Polyamide 6
- PA12 - Halogen Free Polyamide 12
- PU - Polyurethane
- PE - Polyethylene
- NBR - NBR rubber
- PET - Thermoplastic Polyester
- TPV - Thermoplastic



www.pemsa-rejiband.com



Any information included in this document is property of Pemsa®. It cannot be copied, total or partially, nor disclosed to third parties nor used without the explicit and written authorization by Pemsa®. These documents total or partially, can be subject to patent and/or be patent pending and therefore protected by intellectual and industrial property rights. Pemsa, Rejiband, Pemsaband, Inducanal, Rejitech, Megaband, Pemsaflex are registered trademarks property of "Pemsa Cable Management, S.A."