

HM, Haftmuffe, chlorfrei; hellgrau (RAL 7035), grau (RAL 7037) oder orange (RAL 2004), zur dichten Verbindung von Rohren bei Betonverlegung, hellgraue und graue Ausführung nicht flammverbreitend



Material				Temp.		
PE				-25°C/+90°C		
art	dn	ps	pl	ref		
				hellgrau light grey	grau grey	orange orange
HM 16	16,0	100	1200	064 551	027 650	020 608
HM 20	20,0	100	800	064 552	027 651	⇒ KM 20
HM 25	25,0	50	600	064 553	027 652	⇒ KM 25
HM 32	32,0	25	300	064 554	027 653	020 611
HM 40	40,0	25	200	064 555	027 654	020 612
HM 50	50,0	15	120	064 556	027 655	020 613
HM 63	63,0	8	64	064 557	027 656	020 614

HM, clamp type coupler, chlorinefree; light grey (RAL 7035), grey (RAL 7037) or orange (RAL 2004), tight conduit connectors for use in concrete, light grey and grey version non-flame propagating

Zubehör,
PVC, nicht flammverbreitend

Accessories,
PVC, non-flame propagating

SM, Steckmuffe; hellgrau (RAL 7035), grau (RAL 7037), schwarz (RAL 9005) oder weiß (RAL 9010), zur Verbindung von starren oder biegsamen Rohren



Material				Temp.			
PVC-U				-5°C/+60°C		*(-25°C/+60°C)	
art	dn	ps	pl	ref			
				hellgrau light grey	grau* grey*	schwarz black	weiß white
SM 16	16,0	100	1200	020 601	020 594	020 662	020 669
SM 20	20,0	100	800	020 602	020 595	020 663	020 670
SM 25	25,0	50	600	020 603	020 596	020 664	020 671
SM 32	32,0	25	300	020 604	020 597	020 665	020 672
SM 40	40,0	25	200	020 605	020 598	020 666	020 673
SM 50	50,0	15	120	020 606	020 599	020 667	020 674
SM 63	63,0	8	64	020 607	020 600	-	-

SM, slip type coupler; light grey (RAL 7035), grey (RAL 7037), black (RAL 9005) or white (RAL 9010), for the connection of rigid or pliable conduits

SB, Steckbogen, gesickt; hellgrau (RAL 7035), grau (RAL 7037), schwarz (RAL 9005) oder weiß (RAL 9010), zur Verbindung von starren Elektrohröhen im Winkel von 90°



Material				Temp.			
PVC-U				-5°C/+60°C		*(-25°C/+60°C)	
art	dn	ps	pl	ref			
				hellgrau light grey	grau* grey*	schwarz black	weiß white
SB 16	16,0	50	600	020 622	020 615	008 884	009 226
SB 20	20,0	25	300	020 623	020 616	008 885	009 227
SB 25	25,0	10	160	020 624	020 617	008 886	009 228
SB 32	32,0	1	50	020 625	020 618	008 887	009 229
SB 40	40,0	1	35	020 626	020 619	008 889	009 230
SB 50	50,0	1	20	020 627	020 620	008 890	009 231
SB 63	63,0	1	8	065 499	020 621	-	-

SB, normal bend, slip type; light grey (RAL 7035), grey (RAL 7037), black (RAL 9005) or white (RAL 9010), for the connection of rigid conduits in an angle of 90°