

Data sheet

ID	SLXL
Description	CAT8, OM fibre - round-edged DADO trunking, impact resistance 1J
Properties	For the supply of power, data and telecommunication cabling, three fully segregated compartments, further segregation possible by using SLCR cable retainer, special clip-on system for robust connections between trunking body, socket boxes and lid (shock- and child-proof). Suitable for up to CAT7 and CAT8 (UTP & shielded), OM fibre
Colour	white, similar to RAL 9010
Fire Behaviour	non flame propagating
Norms:	EN 50085



Working temperature	UV-Level
-25 to +60 °C °C	L1

Art. no.	Art.	Width x Depth	Small Package	Large Package
104 553	SLXL 65/210 WS 3M	210 x 65 mm	3 m	87 m

Further technical details

Details	
Symmetric	True
Construction type rectangular	False
Halogen free	False
Material	PVC-U

*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.